
H0I98PT2SBUK

12NC: F168258

GTIN (EAN) code: 5054645682584







Product group Commercial code HolgsPT2SBUK Main colour of product Black Construction type Built-in Type of control Type of control Type of controls ettings Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product Sp7 Width of the product Minimum niche height Minimum niche width Niche depth Note of the cavity Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity Trays Pug built-in Black Built-in Built-in Black Built-in Built	MAIN FEATURES	
Main colour of product Construction type Built-in Type of control Type of control Type of control settings Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) - Height of the product Sp7 Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Type Suilt-in Black Built-in B	Product group	0ven
Construction type Type of control Type of control Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) - Height of the product Depth of the product S97 Width of the product S95 Depth of the product Minimum niche height S83 Minimum niche width Niche depth Niche depth S50 Net weight (kg) Usable volume (of cavity) Tipe Control Electronic Electronic Felectronic Total No Electronic Electronic Felectronic Felect	Commercial code	HOI98PT2SBUK
Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Niche depth Net weight (kg) Usable volume (of cavity) To Note descriptions Integrated Cleaning system Plug type Plug type Pyrolytic+Hydrolytic Grids of the cavity	Main colour of product	Black
Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product Depth of the product Depth of the product S97 Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth S50 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Construction type	Built-in
Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product Depth of the product S97 Width of the product Depth of the product Minimum niche height S83 Minimum niche width Niche depth S50 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Type of control	Electronic
Which kind of hobs can be controlled? Automatic programmes Yes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product 597 Width of the product 595 Depth of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width Niche depth 550 Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Type of control settings	-
Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Yes Yes 13 13 11 12 12 13 11 12 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 13 11 11 13 11 11 13 11 11 13 11	Are any hobs controls integrated?	No
Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 130 Plug type UK Depth with open door 90 degree (mm) - Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 130 Plug type UK Depth with open door 90 degree (mm) - Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Automatic programmes	Yes
Frequency (Hz) 50 Length of Electrical Supply Cord (cm) 130 Plug type UK Depth with open door 90 degree (mm) - Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Current (A)	13
Length of Electrical Supply Cord (cm) Plug type Depth with open door 90 degree (mm) Height of the product S97 Width of the product Depth of the product Minimum niche height S83 Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 130 130 130 130 130 130 140 150 150 150 150 150 150 15	Voltage (V)	220-240
Plug type Depth with open door 90 degree (mm) Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) Tall Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Frequency (Hz)	50
Depth with open door 90 degree (mm) Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Length of Electrical Supply Cord (cm)	130
Height of the product 597 Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Plug type	UK
Width of the product 595 Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 583 Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Height of the product	597
Minimum niche height583Minimum niche width560Niche depth550Net weight (kg)39.6Usable volume (of cavity)73Integrated Cleaning systemPyrolytic+HydrolyticGrids of the cavity2	Width of the product	595
Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Depth of the product	564
Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Minimum niche height	583
Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Minimum niche width	560
Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Niche depth	550
Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Net weight (kg)	39.6
Grids of the cavity 2	Usable volume (of cavity)	73
•	Integrated Cleaning system	Pyrolytic+Hydrolytic
Trays 2	Grids of the cavity	2
	Trays	2

TECHNICAL FEATURES	
Timer	Yes
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	No

PERFORMANCES		
Energy input	Electric	
Type of energy of the cavity	Electricity	
Energy efficiency class - NEW (2010/30/EU)	A+	
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.64	
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.87	